




DIN 1460 REFORZADO


HEAVY DUTY



Anillo circular sobre eje



Anillo circular en ranura



Todas las dimensiones en mm

Eje	Ranura (G)					Anillo (F)												Wt. (lb/k)	Te (lb.f)	(i)
S	G	Tol.	W	Tol.	n (mínimo)	d	t	Tol.	D	Tol.	C	C1	L (máximo)	b	h (mínimo)					
12	11.5	+0.00 -0.11	1.60		0.7	0.25	1.50	0.06	11.0	+0.10 -0.36	19.3	18.3	3.4	1.8	1.7	0.75	17.500	1.130		
15	14.3		1.60		1.1	0.35	1.50		13.8		25.1	23.9	4.8	2.0	2.0	1.10	21.900	2.260		
16	15.2		1.60		1.2	0.40	1.50		14.7		26.5	25.2	5.0	2.5	2.0	1.19	23.400	2.410		
17	16.2		1.60		1.5	0.40	1.50		15.7		27.5	26.2	5.0	2.6	2.0	1.39	24.800	3.200		
18	17.0		1.60		1.5	0.50	1.50		16.5		28.7	27.2	5.1	2.7	2.0	1.56	26.300	4.070		
19	17.8		1.60		1.8	0.60	1.50		17.5	+0.13	29.9	28.2	5.2	2.5	2.0	1.45	27.800	4.300		
20	19.0	+0.00	1.85		1.5	0.50	1.75		18.5	-0.42	31.5	30.0	5.5	3.0	2.0	2.19	34.100	4.150		
22	21.0	-0.13	1.85		1.5	0.50	1.75		20.5		34.5	33.0	6.0	3.1	2.0	2.42	37.500	4.980		
23	21.8	+0.00	1.85		1.8	0.60	1.75		21.3		35.7	34.0	6.1	3.2	2.0	2.60	39.200	5.200		
24	22.9		1.85		1.7	0.55	1.75		22.2		37.1	35.5	6.3	3.2	2.0	2.76	40.900	5.880		
25	23.9		2.15		1.7	0.55	2.00		23.2		38.3	36.7	6.4	3.4	2.0	3.59	48.700	6.130		
26	24.4	+0.00	2.15		2.4	0.80	2.00		23.6	+0.21	39.7	37.6	6.6	3.3	2.0	3.65	50.600	7.840		
27	25.5	-0.21	2.15		2.3	0.75	2.00		24.7	-0.42	40.5	38.5	6.5	3.4	2.0	3.85	52.600	7.630		
28	26.6		2.15		2.1	0.70	2.00		25.9		41.5	39.6	6.5	3.5	2.0	4.25	54.500	8.440		
29	27.6		2.15		2.1	0.70	2.00		26.9		42.5	40.6	6.5	3.8	2.0	4.30	56.500	7.650		
30	28.6		2.15		2.1	0.70	2.00		27.9		43.5	41.6	6.5	4.1	2.0	5.35	58.400	9.610		
32	30.3		2.15	+0.14 -0.00	2.6	0.85	2.00	+0.00 -0.07	29.6		45.5	43.3	6.5	4.1	2.5	5.85	62.300	10.200		
33	31.3		2.15		2.5	0.85	2.00		30.5		+0.25	46.9	44.7	6.7	4.0	2.5	5.20	64.300	10.600	
34	32.3		2.65		2.6	0.85	2.50		31.5		+0.25	47.9	45.7	6.6	4.2	2.5	7.05	82.800	12.200	
35	33.0		2.65		3.0	1.00	2.50		32.2		-0.50	48.9	48.4	6.7	4.2	2.5	7.20	85.200	13.200	
36	33.8				2.65	3.3	1.10		2.50		33.0		49.9	47.2	6.7	4.2	2.5	7.50	87.600	14.900
38	36.0	+0.00	2.65		3.0	1.00	2.50		35.2		52.1	49.6	6.8	4.3	2.5	8.30	92.500	15.800		
40	37.5	-0.25	2.65		3.8	1.25	2.50		36.5		55.0	51.5	7.0	4.4	2.5	8.60	80.900	18.800		
42	39.5		2.65		3.8	1.25	2.50		38.5		57.4	53.9	7.2	4.5	2.5	9.30	84.900	19.800		
45	42.5		2.65		3.8	1.25	2.50		41.5		+0.39	61.0	57.5	7.5	4.7	2.5	10.70	91.000	21.200	
48	45.5		2.65		3.8	1.25	2.50		44.5		-0.90	64.6	61.1	7.8	5.0	2.5	11.30	97.100	22.600	
50	47.0		3.15		4.5	1.50	3.00		45.8		67.0	63.0	8.0	5.1	2.5	15.30	121.000	28.300		
52	49.0		3.15		4.5	1.50	3.00	+0.00 -0.08	47.8		69.4	65.4	8.2	5.2	2.5	16.60	126.000	29.400		
55	52.0		3.15		4.5	1.50	3.00		50.8		73.0	69.0	8.5	5.4	2.5	17.10	133.000	31.100		
58	55.0		3.15		4.5	1.50	3.00		53.8		76.6	72.6	8.8	5.6	2.5	18.90	141.000	32.800		
60	57.0		+0.00		3.15	4.5	1.50		3.00		55.8	79.0	75.0	9.0	5.8	2.5	19.40	146.000	33.900	
65	62.0	-0.30	4.15		4.5	1.50	4.00		60.8	+0.46	84.6	80.6	9.3	6.3	3.0	29.10	210.000	36.800		
70	67.0	4.15	4.5		1.50	4.00	65.5		-1.10	90.0	86.0	9.5	6.6	3.0	35.30	226.000	39.600			
75	72.0	4.15	4.5		1.50	4.00	70.5			95.4	91.4	9.7	7.0	3.0	39.30	243.000	42.400			
80	76.5	4.15	5.3		1.75	4.00	74.5		+0.00	100.6	96.1	9.8	7.4	3.0	43.70	259.000	52.800			
85	81.5	+0.00 -0.35	4.15		5.3	1.75	4.00		-0.10	79.5		106.0	101.5	10.0	7.8	3.5	48.50	275.000	56.100	
90	85.5		4.15	5.3	1.75	4.00	84.5		111.4	106.9	10.2	8.2	3.5	59.40	291.000	59.400				
95	91.5		4.15	5.3	1.75	4.00	89.5	+0.54	116.6	112.1	10.3	8.6	3.5	61.20	307.000	62.700				
100	96.5		4.15	5.3	1.75	4.00	94.5	-1.30	122.0	117.5	10.5	9.0	3.5	71.60	324.000	66.000				

Con fondo amarillo se mantiene stock

