




DIN 1460 REFORZADO

HEAVY DUTY



Anillo circular sobre eje

Anillo circular en ranura

Todas las dimensiones en mm

Ej e	Ranura (G)					Anillo (F)											Wt. (lb/k)	T (lb)
S	G	Tol.	W	Tol.	n (mínimo)	d	t	Tol.	D	Tol.	C	C1	L (máximo)	b	h (mínimo)			
12	11.5	+0.00 -0.11	1.60		0.7	0.25	1.50	0.06	11.0	+0.10 -0.36	19.3	18.3	3.4	1.8	1.7	0.75	17.	
15	14.3		1.60		1.1	0.35	1.50		13.8		25.1	23.9	4.8	2.0	2.0	1.10	21.	
16	15.2		1.60		1.2	0.40	1.50		14.7		26.5	25.2	5.0	2.5	2.0	1.19	23.	
17	16.2		1.60		1.5	0.40	1.50		15.7		27.5	26.2	5.0	2.6	2.0	1.39	24.	
18	17.0		1.60		1.5	0.50	1.50		16.5		28.7	27.2	5.1	2.7	2.0	1.56	26.	
19	17.8	+0.00 -0.13	1.60		1.8	0.60	1.50	0.06	17.5	+0.13 -0.42	29.9	28.2	5.2	2.5	2.0	1.45	27.	
20	19.0		1.85		1.5	0.50	1.75		18.5		31.5	30.0	5.5	3.0	2.0	2.19	34.	
22	21.0		1.85		1.5	0.50	1.75		20.5		34.5	33.0	6.0	3.1	2.0	2.42	37.	
23	21.8		1.85		1.8	0.60	1.75		21.3		35.7	34.0	6.1	3.2	2.0	2.60	39.	
24	22.9	+0.00 -0.21	1.85		1.7	0.55	1.75	0.06	22.2	+0.21 -0.42	37.1	35.5	6.3	3.2	2.0	2.76	40.	
25	23.9		2.15		1.7	0.55	2.00		23.2		38.3	36.7	6.4	3.4	2.0	3.59	48.	
26	24.4		2.15		2.4	0.80	2.00		23.6		39.7	37.6	6.6	3.3	2.0	3.65	50.	
27	25.5		2.15		2.3	0.75	2.00		24.7		40.5	38.5	6.5	3.4	2.0	3.85	52.	
28	26.6	+0.00 -0.25	2.15		2.1	0.70	2.00	0.06	25.9	+0.25 -0.50	41.5	39.6	6.5	3.5	2.0	4.25	54.	
29	27.6		2.15		2.1	0.70	2.00		26.9		42.5	40.6	6.5	3.8	2.0	4.30	56.	
30	28.6		2.15		2.1	0.70	2.00		27.9		43.5	41.6	6.5	4.1	2.0	5.35	58.	
32	30.3		2.15		2.6	0.85	2.00		29.6		45.5	43.3	6.5	4.1	2.5	5.85	62.	
33	31.3	+0.00 -0.39	2.15	+0.14 -0.00	2.5	0.85	2.00	+0.00 -0.07	30.5	+0.25 -0.50	46.9	44.7	6.7	4.0	2.5	5.20	64.	
34	32.3		2.65		2.6	0.85	2.50		31.5		47.9	45.7	6.6	4.2	2.5	7.05	82.	
35	33.0		2.65		3.0	1.00	2.50		32.2		48.9	48.4	6.7	4.2	2.5	7.20	85.	
36	33.8		2.65		3.3	1.10	2.50		33.0		49.9	47.2	6.7	4.2	2.5	7.50	87.	
38	36.0	+0.00 -0.25	2.65		3.0	1.00	2.50	0.06	35.2	+0.39 -0.90	52.1	49.6	6.8	4.3	2.5	8.30	92.	
40	37.5		2.65		3.8	1.25	2.50		36.5		55.0	51.5	7.0	4.4	2.5	8.60	80.	
42	39.5		2.65		3.8	1.25	2.50		38.5		57.4	53.9	7.2	4.5	2.5	9.30	84.	
45	42.5		2.65		3.8	1.25	2.50		41.5		61.0	57.5	7.5	4.7	2.5	10.70	91.	
48	45.5	+0.00 -0.30	2.65		3.8	1.25	2.50	0.06	44.5	+0.46 -1.10	64.6	61.1	7.8	5.0	2.5	11.30	97.	
50	47.0		3.15		4.5	1.50	3.00		45.8		67.0	63.0	8.0	5.1	2.5	15.30	121.	
52	49.0		3.15		4.5	1.50	3.00		47.8		69.4	65.4	8.2	5.2	2.5	16.60	126.	
55	52.0		3.15		4.5	1.50	3.00		50.8		73.0	69.0	8.5	5.4	2.5	17.10	133.	
58	55.0	+0.00 -0.30	3.15		4.5	1.50	3.00	-0.08	53.8	+0.46 -1.10	76.6	72.6	8.8	5.6	2.5	18.90	141.	
60	57.0		3.15		4.5	1.50	3.00		55.8		79.0	75.0	9.0	5.8	2.5	19.40	146.	
65	62.0		4.15		4.5	1.50	4.00		60.8		84.6	80.6	9.3	6.3	3.0	29.10	210.	
70	67.0		4.15		4.5	1.50	4.00		65.5		90.0	86.0	9.5	6.6	3.0	35.30	226.	
75	72.0	+0.00 -0.30	4.15		4.5	1.50	4.00	0.06	70.5	+0.46 -1.10	95.4	91.4	9.7	7.0	3.0	39.30	243.	

80	76.5		4.15		5.3	1.75	4.00	+0.00	74.5		100.6	96.1	9.8	7.4	3.0	43.70	259
85	81.5		4.15		5.3	1.75	4.00	-0.10	79.5		106.0	101.5	10.0	7.8	3.5	48.50	275
90	85.5	+0.00	4.15		5.3	1.75	4.00		84.5		111.4	106.9	10.2	8.2	3.5	59.40	291
95	91.5	-0.35	4.15		5.3	1.75	4.00		89.5	+0.54	116.6	112.1	10.3	8.6	3.5	61.20	307
100	96.5		4.15		5.3	1.75	4.00		94.5	-1.30	122.0	117.5	10.5	9.0	3.5	71.60	324

Con fondo amarillo se mantiene stock

